



255 Wooster Road North • Barberton, Ohio 44203  
Phone: (330) 745-9016 • Fax: (330) 745-4886  
www.tahomarubberplastics.com

## **LDPE REPRO**

These products are reprocessed PE resins suitable for a variety of applications including: Sheet/Profile Extrusion, Film (Cast or Other) and Injection Molding. Product types include: Black, Natural, Mixed Color and Mixed Color/Black Camelback Repro.

### **Typical Properties**

Density:	.92 ± .02 gms/cm
Melt Index	1.00 – 3.00 gms/10 Minutes
Moisture	0.2% maximum
Contamination	Strained at 100 mesh minimum
Pellet Quality	Classified, Clean free flow cut
Packaging	1000 lb Poly lined gaylords

### **Typical Applications**

Profile Extrusion: Lawn Edging, Pipe, Mudflaps & Miscellaneous/ Other

Film Extrusion: Agriculture, Trash Bags, etc

### **Special Features**

Repro Resins are designed to accept easy coloring by our complimentary ECONO-BLAK Concentrate. Call for additional information.

The Technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risks of use, storage and handling of product. **No warranty, express or implied, is made including, but not limited to, implied warranties of merchantability and fitness for a particular purpose.** Nothing contained herein shall be construed as a license to operate under, or recommended to infringe, any patents.